

# GCT External Pump

**Allows Gas Clip diffusion detectors to take remote samples from up to 75 feet away**



- Compatible with all GCT multi gas and single gas diffusion detectors
- Draws samples at greater than 1 ft. per second (using 1/8" ID tubing)
- 40-hour continuous run time (typically)
- Rechargeable battery (charger included)
- 4 to 6-hour recharge time (typically)
- Users can perform manual block tests
- Audio & visual alerts for blockages and low battery
- IP 68 rating to withstand the harshest environment

**gasclip**  
technologies

Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808

Contact us: <https://www.gascliptech.com/contactus.php>



## GCT External Pump Version

### GCT External Pump

Part# GCT-XP

External pump for drawing gas samples. Compatible with all GCT diffusion gas detectors.

Included with device: charger, ten foot sampling hose, three foot connecting hose, stainless steel diffusion stone, ten additional filters (five hydrophobic & five particulate) and Quick Start Guide.

## GCT External Pump Accessories



**6ft. Telescoping Sampling Probe**  
Part# PROBE-TS



**MGC Remote Sampling Probe**  
Part# PROBE-1



**MGC Pump Quick Disconnect\***  
Part# MGC-PUMP-QD



**MGC Multi Charger**  
Part# MGC-CHARGER-MULTI



**MGC Vehicle Charger**  
Part# MGC-CHARGER-V



**Hose By The Foot**  
Part# HOSE-FT



**Confined Space Kit**  
Part# CSK-XP  
GCT EXTERNAL PUMP Included






**Confined Space Kit w/ Gas**  
Part# CSK-XP-GAS  
GCT EXTERNAL PUMP Included

\*Detector sold separately.

Please contact us for additional accessories and spare parts.

**Distributed by:**

## SPECIFICATIONS

<b>Size - Weight</b>	6.4" H x 2.6" W x 1.25" D (163 x 68 x 31mm) • 8 oz (235g)
<b>Temperature</b>	-7.6° to +122°F (-22° to +50°C)
<b>Humidity</b>	5% to 100% RH (non-condensing)
<b>Battery Life</b>	40 continuous hours (typically)
<b>Charge Time</b>	4 - 6 hours (typically)
<b>Alarms</b>	Visual & audible (minimum 95 dB)
<b>LED's</b>	<p><u>Pump Flow LED</u>--indicates that the pump is on and/or blocked</p> <p><u>Power LED</u>--indicates that the pump is on and the amount of battery life remaining</p> <p><u>Battery LED</u>--indicates when the pump is charging and when it is fully charged</p>
<b>Tests</b>	Full-function self test upon activation Battery test runs continuously
<b>Ratings</b>	IP 68
<b>Gas Inlet</b>	1/8 in. Stainless steel barbed fitting
<b>Pump Draw</b>	Sample from up to 75 ft. (23 m)
<b>Sample Delay Time</b>	Less than 1 second per 1 ft. (0.3m) with 1/8 in. ID tubing
<b>Certifications and Approvals</b>	<p> <b>CSA:</b> C22.2 No. 152; CSA21CA80033769X ANSI/ISA S12.13.01 Intrinsically Safe/Sécurité Intrinsèque Class I, Division 1, Group A, B, C, &amp; D, T4 Class I, Zone 0, AEx ia IIC T4 Ga -20°C ≤ Ta ≤ +50°C; 4.2 Vdc</p> <p> <b>IECEx:</b> IECEx CSA 21.0006X Ex ia IIC T4 Ga IEC 60079-0:2017 IEC 60079-11:2011 -20°C ≤ Ta ≤ +50°C; 4.2 Vdc</p> <p> <b>ATEX:</b> CSANe 21ATEX2143X CE 2813 II 1 G Ex ia IIC T4 Ga EN 60079-0:2018 EN 60079-11:2012 -20°C ≤ Ta ≤ +50°C; 4.2Vdc</p>
<b>Warranty</b>	Full 2 years



Specifications are subject to change without notice due to ongoing product development.

Copyright © 2023 Gas Clip Technologies, Inc. All Rights Reserved

DS-GCT-XP v1.08